

EyeSafe 40 Micron Core Holmium-Doped LMA Double Clad Fiber

True LMA fiber featuring a unique low NA (< 0.1) high concentration Ho-doped core design. The Ho-doped fiber can be pumped by a Tm-doped fiber laser at ~ 1950 -nm and can achieve 60% efficiency. The high NA (0.46) large pump cladding waveguide allows for efficient coupling of high pump powers. The large core diameter ($40 \mu m$) maintains a large mode field diameter and short device length, thereby minimizing non-linear effects such as SBS and SRS.

Typical Applications

- High power CW and pulsed
- EyeSafe (~2 µm) lasers and amplifiers
- · Military and commercial LIDAR
- ~2 µm output TEM₀₀ fiber lasers for pumping solid state crystal lasers

Features & Benefits

- Unique low NA Ho-doped core design Robust single-mode beam quality
- NuCOAT™ fluoroacrylate coating Greater fiber durability in extreme environmental operating & storage conditions
- High pump absorption Short fiber length, efficient lasing in the ~2 μm window

Optical Specifications

Operating Wavelength
Core NA
First Cladding NA (5%)
Cladding Attenuation
Cladding Absorption

LMA-HDF-40/400

2100 - 2200 nm 0.080 ± 0.010 ≥ 0.46 $\leq 15.0 \text{ dB/km} @ 810 \text{ nm}$ $0.30 \pm 0.20 \text{ dB/m} \text{ at } 1150 \text{ nm}$

Geometrical & Mechanical Specifications

Cladding Diameter (flat-to-flat)
Core Diameter
Coating Diameter
Core/Clad Offset
Prooftest Level

 $400.0 \pm 10.0 \,\mu\text{m}$ $40.0 \pm 4.0 \,\mu\text{m}$ $550.0 \pm 15.0 \,\mu\text{m}$ $\leq 2.00 \,\mu\text{m}$ $\geq 100 \,\text{kpsi} \,(0.7 \,\text{GN/m}^2)$



