400 Micron Core Power Delivery Fibers



Coherent's specialty multimode step-index fibers are designed for compatibility with the majority of fiber-coupled, bar and stack diode-laser packages and support the diode laser power delivery market. These power delivery fibers are available in 400/440 and 400/480 core/clad ratios in low and high NA versions. The 400/480 has a low refractive index fluoroacrylate coating for added power confinement. Other fiber diameters are available upon request.

Typical Applications

Features & Benefits

- Fiber coupled diode lasers
- Couplers and pump combiners
- 0.12 and 0.22 NA Compatible with majority of fiber-coupled, diode-laser packages
- Exceptional geometric uniformity and core/clad concentricity Ease of coupling to pump diodes

Optical Specifications	MM-S400/440-12A	MM-S400/440-22A	MM-S400/480-22FA
Operating Wavelength	800 – 1600 nm	800 – 1600 nm	800 – 1600 nm
Core NA	0.120 ± 0.020	0.220 ± 0.020	0.220 ± 0.020
First Cladding NA (5%)	N/A	N/A	≥ 0.46
OH Level	Low	Low	Low
Geometrical & Mechanical Specifications			
Cladding Diameter	440.0 ± 8.0 μm	440.0 ± 8.0 μm	480.0 ± 8.0 μm
Core Diameter	400.0 ± 9.0 µm	400.0 ± 9.0 μm	400.0 ± 9.0 μm
Coating Diameter	625.0 ± 25.0 μm	625.0 ± 25.0 μm	640.0 ± 25.0 μm
Core/Clad Offset	≤ 5.00 µm	≤ 5.00 µm	≤ 5.00 µm
Coating Material	Acrylate	Acrylate	Low Index Acrylate
Prooftest Level	≥ 100 kpsi (0.7 GN/m²)	≥ 100 kpsi (0.7 GN/m²)	≥ 100 kpsi (0.7 GN/m²)

COHERENT,

Nufern • 7 Airport Park Road, East Granby, CT 06026 • 860.408.5000 • Toll-free 866.466.0214 • Fax 860.844.0210 • Email: tech.sales@coherent.com www.coherent.com ; www.shop.coherent.com • Coherent products are manufactured under an ISO 9001:2008 certified quality management system.



Custom developed fiber (FUD) specifications are subject to change without notice. Other configurations such as alternative form factors, optimized cut-off and UV cured color coating may be available. Let us know how Coherent can assist with your requirements.