30/400 Passive LMA Double Clad Fibers



Coherent's passive series of Large Mode Area (LMA) double clad fibers are ideal for high power monolithic fiber lasers and amplifiers. These passive fibers are based on a 30 micron diameter core and 400 micron diameter clad size with a low NA (0.06) core and are designed to work well with the active Yb-doped 30/400 LMA fibers. These fibers utilize the latest fiber design and NuCOATTM coating technology to ensure excellent preservation of beam quality and extended operating life at the high power levels demanded by today's industrial fiber laser applications. These fibers are available in both non-PM and PANDA-style PM fibers.

Typical Applications

- Monolithic high power lasers & amplifiers
- LMA fiber couplers & pump combiners
- · High power pump & signal pigtails
- · Military, industrial and medical

Features & Benefits

- Designed for compatibility with 30/400 active fibers
- NuCOAT™ fluoroacrylate coating Greater fiber durability in extreme environmental operating & storage conditions
- Optimized LMA core design Easy to maintain single mode LP01 beam through fiber & components at high power
- All fiber proof tested to > 100 kpsi Critical for ensuring long term reliability when coiling

Optical Specifications

Operating Wavelength
Core NA
First Cladding NA (5%)
Cladding Attenuation
Birefringence

Geometrical & Mechanical Specifications

Cladding Diameter Core Diameter Coating Diameter Prooftest Level

PLMA-GDF-30/400 LMA-GDF-30/400

1060 - 1600 nm 1060 - 1600 nm 0.060 ± 0.010 0.060 ± 0.010 ≥ 0.46

 \leq 15.0 dB/km @ 1095 nm \leq 15.0 dB/km @ 1095 nm

nominal 3×10^{-4} N/A

 $\begin{array}{lll} 400.0 \pm 10.0 \; \mu m & 400.0 \pm 10.0 \; \mu m \\ 30.0 \pm 2.5 \; \mu m & 30.0 \pm 2.5 \; \mu m \\ 550.0 \pm 20.0 \; \mu m & 550.0 \pm 20.0 \; \mu m \\ \geq 100 \; kpsi \; (0.7 \; GN/m^2) & \geq 100 \; kpsi \; (0.7 \; GN/m^2) \end{array}$



Designed to work with 30/400 LMA Yb-doped active fibers.



