10/130 Ytterbium-Doped LMA Double Clad Fiber



Featuring the latest Gen VIII glass composition, Coherent's large mode area (LMA) and PM-LMA Ytterbium-doped double clad fibers are ideally suited for applications spanning military, industrial and medical including linearly polarized fiber lasers and amplifiers. LMA Yb-doped fibers enable efficient, compact, diode pumped fiber sources that are an attractive alternative to traditional solid-state lasers. This fiber features a single mode large core/cladding ratio with a low NA and is ideally suited for both CW and pulsed laser applications.

Typical Applications

- Pulsed fiber lasers and amplifiers
- · Material processing
- LIDAR
- Non-linear optics / frequency doubling

Features & Benefits

- NuCOAT fluoroacrylate coating Greater fiber durability in extreme environmental operating & storage conditions
- LMA core design and short amplifier length Useful for generating high peak powers
- Easy to maintain single mode LP01 beam through fiber & components
- PANDA-style stress structure for increased birefringence Superior optical performance and uniformity
- All fiber proof tested to > 100 kpsi Critical for ensuring long term reliability when coiling

Optical Specifications

Operating Wavelength
Core NA
First Cladding NA (5%)
Cladding Attenuation
Cladding Absorption

Birefringence

Geometrical & Mechanical Specifications

Cladding Diameter
Core Diameter
Coating Diameter
Core/Clad Offset
Coating Material
Prooftest Level

PLMA-YDF-10/125-VIII LMA-YDF-10/130-VIII

1015 − 1115 nm 1015 - 1115 nm 0.075 0.075 ≥ 0.460 ≥ 0.46

 \leq 15.0 dB/km @ 1095 nm \leq 15.0 dB/km @ 1095 nm 1.60 \pm 0.20 dB/m at 915 nm 1.40 \pm 0.30 dB/m at 915 nm 4.80 dB/m near 976 nm nominal 3×10^{-4} N/A

 $\begin{array}{lll} 125.0 \pm 2.0 \ \mu m & 130.0 \pm 3.0 \ \mu m \\ 11.0 \pm 1.0 \ \mu m & 11.0 \pm 1.0 \ \mu m \\ 245.0 \pm 15.0 \ \mu m & 245.0 \pm 15.0 \ \mu m \\ \leq 1.00 \ \mu m & \leq 1.00 \ \mu m \\ \text{Low Index Acrylate} & \text{Low Index Acrylate} \\ \geq 100 \ \text{kpsi} \ (0.7 \ \text{GN/m}^2) & \geq 100 \ \text{kpsi} \ (0.7 \ \text{GN/m}^2) \end{array}$



The precision matched fiber sets are also available - see PLMA-YDF-10/125-M; LMA YDF-10/130-M; PLMA-GDF-10/125-M and LMA-GDF-10/130-M

Nufern • 7 Airport Park Road, East Granby, CT 06026 • 860.408.5000 • Toll-free 866.466.0214 • Fax 860.844.0210 • Email: tech.sales@coherent.com www.coherent.com; www.shop.coherent.com • Coherent products are manufactured under an ISO 9001:2008 certified quality management system.

