Photosensitive 980 nm Polarization Maintaining Fiber



Coherent photosensitive 980 nm polarization maintaining fiber is designed to perform all functions of a 980 nm PM fiber but with enhanced photosensitivity for fabrication of gratings. This fiber is designed for use in pump diodes, couplers and multiplexers. PS-PM980 allows component manufacturers to make low cost fibertails for 980 nm pumps. Using one fiber that provides excellent photosensitivity, as well as polarization maintaining attributes, substantially reduces writing time thus lowering costs.

Typical Applications

- Grating-based pump diode pigtails
- Couplers
- Multiplexers

Features & Benefits

- PANDA-style stress structure for increased birefringence Superior optical performance and uniformity
- · High photosensitivity Enables low cost, high yield grating fabrication
- Tightly controlled specifications Excellent uniformity

Optical Specifications

Operating Wavelength 97

Core NA
Mode Field Diameter
Cutoff

Core Attenuation

Beat Length

Normalized Cross Talk

PS-PM980

970 – 1550 nm 0.120

6.6 ± 1.0 µm @ 980 nm 900 ± 70 nm

≤ 3.0 dB/km @ 980 nm ≤ 3.5 mm @ 980 nm

≤ - 40.0 dB at 4 m @ 980

nm

≤ - 25.0 dB at 100 m @

980 nm

Geometrical & Mechanical Specifications

Cladding Diameter
Core Diameter
Coating Diameter
Coating Concentricity
Core/Clad Offset
Coating Material
Operating Temperature Range

Coating Material
Inperature Range
Prooftest Level

 $125.0 \pm 1.0 \ \mu m$ $6.0 \ \mu m$ $245.0 \pm 15.0 \ \mu m$ $< 5.0 \ \mu m$ $\le 0.50 \ \mu m$ Acrylate

-40 to 85 °C

≥ 100 kpsi (0.7 GN/m²)



