Planar Waveguide Single-Mode Fiber



Coherent extra high-performance Planar Waveguide Fiber is part of the NuBRIDGE™ fiber family and provides a solution to the splicing challenges for high NA waveguiding structures. Industry developments indicate the call out for easy interfacing of new planar waveguide (PWG) technology with existing fiber infrastructures. Planar Waveguide Fiber is an excellent bridge fiber between high NA planar waveguides and low NA transmission fiber. This fiber allows outstanding optical coupling with planar waveguides. In addition, the composition of PWG1-XP is tailored to thermally expand the core during splicing and thus achieve low splice loss to transmission fibers.

Typical Applications

- Fibertails for Planar Waveguides
- Bridge Fiber
- · Silicon photonics devices

Features & Benefits

- High numerical aperture Bend insensitive fiber for miniature packages
- Thermally expandable core Low splice loss to transmission fiber
- Small Mode Field Diameter High coupling efficiency with Planar Waveguides

Optical Specifications

Operating Wavelength Core NA Mode Field Diameter

Cutoff

PWG1-XP

1350 – 1600 nm 0.260 4.8 ± 0.5 μm @ 1550 nm 1330 ± 50 nm

Geometrical & Mechanical Specifications

Cladding Diameter
Core Diameter
Coating Diameter
Coating Concentricity
Core/Clad Offset
Coating Material
Operating Temperature Range
Short Term Bend Radius
Long Term Bend Radius
Prooftest Level

125.0 ± 0.5 μ m 3.7 μ m 245.0 ± 10.0 μ m < 5.0 μ m ≤ 0.30 μ m Acrylate -55 to 85 °C ≥ 6 mm ≥ 13 mm

≥ 200 kpsi (1.4 GN/m²)



